



P6217W

21.5" FHD TFT Widescreen Industrial LCD Monitor

NEW



- | | |
|--------------------|---|
| 1. T/S port | 4. DVI-D |
| 2. Audio (Line-in) | 5. HDMI |
| 3. VGA | 6. Screw type or phoenix type power input |

Features

- 21.5" TFT 250 nits FHD LCD with projective capacitive multi-touch
- NEMA 4/12 (IP65)-compliant flat panel monitor
- Supports panel mount, wall mount and VESA mount
- Supports full range screw-type (locked) AC-in or 24V DC-in (option)
- VGA, HDMI and DVI with multi-signal inputs supported



Introduction

The P6217W is a slim-type industrial LCD monitor with flat front bezel design, which adopts 21.5-inch 250 nits full HD LCD display and supports multi-signal interfaces including DVI, VGA, S-Video, Video. Featuring IP65 (NEMA 4)-rated front bezel, screw-type adaptor plug design, and 12/24V DC-In, the 12.1-inch P6121 is designed to fit for all kinds of industrial environments. Moreover, the P6217W supports panel mount, wall mount or VESA FPMPMI (Video Electronics Standards Association Flat Panel Monitor Physical Mounting Interface) mounting. With the compact mechanism design, the P6217W can be deployed easily in any space-limited place. It is especially suitable for POI/POS, HMI and all kinds of heavy-duty industrial fields.

Specifications

Front Bezel	NEMA 4/12 (IP65)-compliant, flat front bezel	
Mounting	Supports panel mount, wall mount and VESA mount FPMPMI mounting (video electronics standards association Flat Panel monitor physical mounting interface)	
LCD Panel	Display	21.5" TFT FHD LCD
	Max. Resolution	1920 x 1080
	Max. Colors	16.7M
	Active Area (mm)	476.64 x 268.11
	Pixel Pitch (mm)	0.24 x 0.24
	Response Time	18 ms
	Backlight	LED
	Backlight MTBF	50,000 hrs
	Viewing Angle (H/V)	178°/178°
	Contrast Ratio	3000 (TYP.)
Brightness (cd/m ²)	250 nits	
Display Control	OSD (on screen display)	
Display Mode	VGA 640 x 350 (70Hz), VGA 640 x 480 (60/72/75Hz), VGA 720 x 400 (70Hz), SVGA 800 x 600 (60/72/75Hz), XGA 1024 x 768 (60/72/75Hz), WXGA 1366 x 768 (60Hz), FHD 1920 x 1080 (60Hz)	



Specifications

Input Signal	VGA HDMI DVI (only for DVI-D) Touchscreen: USB interface
I/O Connectors	1 x USB for touchscreen version 1 x Audio (Line-in) 1 x VGA input 1 x HDMI 1 x DVI 1 x Screw type or phoenix type power input
Power Adapter	Screw-type external AC/DC power adapter
Power Consumption	TBD
Touchscreen	Multi-touch projective capacitive (optional)
Dimensions	547.59 mm (21.56") (W) x 339.05 mm (13.34") (D) x 53 mm (2.09") (H)
Packing Dimensions	700 mm (27.56") (W) x 185 mm (7.28") (D) x 510 mm (20.07") (H)
Weight (net/gross)	TBD
Environment	Operating temperature: 0°C ~ +45°C (+32°F ~ +113°F) Storage temperature: 0°C ~ +50°C (+32°F ~ +122°F) Relative humidity: 20%~90% @ 40°C, non-condensing
Certificate	CE

Ordering Information

P6217W		
AC Power	Panel mount monitor	
	Capacitive (USB)	P6217WPC-AC-U-US-EU
	Glass	P6217WPG-AC-US-EU
24VDC Power	Panel mount monitor	
	Capacitive (USB)	P6217WPC-24VDC-U
	Glass	P6217WPG-24VDC

Overview

Fanless Touch Panel Computers

Heavy-duty Fanless Touch Panel Computers

Industrial Touch Panel Computers

4

Industrial Touch panel Monitors

Infotainment Touch Panel Computers

Healthcare & Medical Solutions

Open Frame Panel Computers

Accessories

Dimensions

